

# Data sheet

## Table Top Workstation UFM 03/200/200

with separate control cabinet | Art. No. 70503202001M

Performance data	
Rated Force	3000 N
Stroke	200 mm
Nominal speed	200 mm/s
Service life / operating life	10 years
Max. shutdown time (time to safe condition)	0,2 ms – without tools
Sound emission	Sound pressure level $\leq$ 85 dB
Mechanical data	
Dimensions (H x D x W) W and D – with PC support arm extended to maximum	1225 x 1330 x 1550 mm
Weight incl. cabinet	125 kg
Drive carrier	4-Column frame
Control cabinet (H x D x W)	800 x 400 x 600 mm
Electrical data	
Mains voltage	400 VAC +/-10%
Frequency	50 Hz +/-10%
Power input	11,9 kVA
Environmental data / Environmental conditions	
Temperature range	Operation: +/-0°...+40°C Storage: -10°...+50°C
Protection class for switch cabinet	IP 54
Area of application	Industrial environment
Permitted tools	
Minimum distance required from moving parts	200 mm
Max. tool weight	30 kg
Power generator / drive	
Type	Line5s
Power	0,88 kW
Rotary encoder	
Type	SINCOS
Accuracy	45 seconds of arc
Servo amplifier	
Type	UNIDRIVE M702



For more efficiency.

